602.3505-443

MULTI -WAY ADAPTOR
IP66 32A 3P+E 400V



* Product image may be indicative

IEC 60309-1 (2021)
IEC 60309-2 (2021)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	ADAPTO Series
Synthetical description	MULTI -WAY ADAPTOR
Description	

The ADAPTO Series multi-way adaptor is engineered for demanding industrial environments, featuring a robust 2-meter H07RN-F rubber cable. It supports a 3P+E configuration, accommodating a rated current of 32A and a rated voltage of 400V. Constructed from high-quality thermoplastic, it ensures durability and longevity. With an IP66 protection degree, it offers superior protection against dust and water ingress. The unit is equipped with a PG21 cable gland, cable clamp, and terminal block, and includes a zinc-plated steel carrying handle. The OPTIMA-REVERSE plug with phase inverter enhances operational flexibility, making it a reliable choice for industrial applications.

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Rated voltage	400V
Cable section	2,5mm²
Cable	H07RN-F

PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Protection degree IP	IP66

DIMENSIONAL CHARACTERISTICS

Cable length	2m

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Zinc-plated steel carrying handle.
	Plug OPTIMA-REVERSE with phase inverter.
	Equipped with PG21 cable gland, cable clamp and terminal block.
	2m rubber cable H07RN-F