644.0345

SURFACE MOUNTING BOX
122x120x90mm IP66 GW 960°C
COMPONENT BLACK
THERMOSETTING



* Product image may be indicative

EN 60079-31 (2014)
IEC 60079-0 (2017)
IEC 60079-31 (2013)
EN 60079-7 (2015)
EN IEC 60079-7/A1 (2018)
IEC 60079-7/AMD1 (2017)
IEC 60079-31 (2022)
EN IEC 60079-0 (2018)
IEC 60079-7 (2015)

ATEX directive 2014/34/EU

GENERAL CHARACTERISTICS

Commercial Series	ZENITH-P Series
Synthetical description	SURFACE MOUNTING BOX

EX CHARACTERISTICS

Group and categories EX	II 2GD
Modo protezione gas	Ex eb IIC Gb
Dust protection	Ex tb IIIC Db IP66

PHYSICAL CHARACTERISTICS

Protection degree	Splash proof
Protection degree IP	IP66
Material	THERMOSETTING
Impact resistance	7J
Equipment	Empty enclosure
GLOW WIRE	GW 960°C
Colour	BLACK
Ambient temperature Ta min	-60 °C
Ambient temperature Ta max	100 °C

DIMENSIONAL CHARACTERISTICS

Dimensions	122x120x90mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual
Instruction manual
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.