656.0026-000

EMPTY ENCLOSURE
IP66 16 DIN (2x8) 440x365x290mm 6 OPTIMA



* Product image may be indicative

EN 62208 (2011-10)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	MBOX2 Series
Synthetical description	EMPTY ENCLOSURE

TECHNICAL CHARACTERISTICS

Dissipable power	29W

PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Protection degree IP	IP66
Protection degree IK	IK09

DIMENSIONAL CHARACTERISTICS

N.° modules	16 DIN (2x8)
Dimensions	440x365x290mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Notes	6 OPTIMA
Catalogue notes	Power dissipation calculated in conformity with IEC EN 62208 and IEC EN 60670-24 standards
	MBOX turns on a new era with a box that is even more functional and complete. The addition of an automatic device (LED with extremely low consumption hooked up to a sensor) ensures proper lighting of the compartment containing outlets and switch gear and protection devices when the outdoor light intensity diminishes. This allows the product to be identified and used under conditions of poor lighting: ideal for the worksite, MBOX is also perfect for campsites and parking areas. Extremely compact and totally safe, MBOX features an innovative design and it is made in collision-proof and self-extinguishing technopolymer, to withstand collisions and atmospheric agents. In compliance with the highest safety standards, the MBOX series includes a complete product range and comes in many customized versions, with fast delivery.
	With cut-outs to contain 16A (70x87mm) socket or, with suitable adaption, 32A (84x106mm) socket and DOMOPLUS Series