672.5416

MODULAR ENCLOSURE
IP66 SURFACE MOUNTING M550 16 MOD. 328x550x140mm GREY



* Product image may be indicative

EN 60670-1 (2005)
EN 60670-24 (2013)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	DOMINO IP66 Series [enclosure]
Synthetical description	MODULAR ENCLOSURE
Description	

The DOMINO IP66 Series modular enclosure is engineered for robust performance in demanding environments. Constructed from durable thermoplastic, it offers a protection degree of IP66 and IK08, ensuring resilience against dust, water, and mechanical impacts. Designed for surface mounting, this enclosure accommodates 16 modules and features dimensions of 328x550x140mm. The enclosure is grey in color and includes a connection device to be fixed in the upper side. Power dissipation is calculated in accordance with IEC EN 62208 and IEC EN 60670-24 standards, ensuring compliance with international safety and performance regulations. Discover the new application directly on the web at www.scame.com/Combiwizard.asp. Identifies the products compatible with pre-drilled enclosures SCAME!

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Dissipable power	28W

PHYSICAL CHARACTERISTICS

Colour	GREY
Material	THERMOPLASTIC
Mounting version	SURFACE MOUNTING
Protection degree IP	IP66
Protection degree IK	IK08

DIMENSIONAL CHARACTERISTICS

Modularity	M550
N.° modules	16 MOD.
Dimensions	328x550x140mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	Connection device to be fixed in the upper side.
	Power dissipation calculated in conformity with IEC EN 62208 and IEC EN 60670-24 standards
	ScameOnLine Discover the new application directly on the web, www.scame.com/Combiwizard.asp Identifies the products compatible with pre-drilled enclosures SCAME!

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000