679.1002

CONSUMER UNIT
IP66 SURFACE MOUNTING 2 DIN 2 MOD. 71x140x100mm GREY



* Product image may be indicative

EN 60670-24 (2013)
EN IEC 60670-1 (2021)
EN IEC 60670-1/A11 (2021)
EN 60670-24/A11 (2023)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	IKONA Series
Synthetical description	CONSUMER UNIT

Description

The IKONA Series consumer unit is engineered for robust performance in demanding environments. Designed for surface mounting, it accommodates 2 modules and is constructed from durable thermoplastic material. The unit, with 71x140x100mm dimensions, is finished in grey and offers a high protection degree of IP66, ensuring resistance to dust and powerful water jets, while the IK09 rating provides impact resistance. Power dissipation is calculated in accordance with IEC EN 62208 and IEC EN 60670-24 standards, ensuring compliance with international safety and performance regulations.

Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Dissipable power	6W

PHYSICAL CHARACTERISTICS

Colour	GREY
Material	THERMOPLASTIC
Halogen free	HALOGEN FREE
Mounting version	SURFACE MOUNTING
Protection degree IP	IP66
Protection degree IK	IK09

DIMENSIONAL CHARACTERISTICS

Modularity	2 DIN
N.° modules	2 MOD.
Dimensions	71x140x100mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	Power dissipation calculated in conformity with IEC EN 62208 and IEC EN 60670-24 standards