

746.4000-011

DOMESTIC CABLE REEL
IP20 40m 3x1,5mm²



EN 61242 A1 (2008)

EN 61242 (1997)

EN 61242 A2 (2016)

EN 61242 A13 (2017)

Low voltage direct. 2014/35/EU

DIRECTIVE RoHS 2011/65/EU

■ GENERAL CHARACTERISTICS

Commercial Series	ROLLER 330 Series
Synthetical description	DOMESTIC CABLE REEL
Description	The ROLLER 330 Series domestic cable reel is engineered for demanding electrical environments. Constructed from robust engineering plastic, it features a 40-meter H05VV-F cable with a section of 1.5mm ² , ensuring efficient and reliable electrical transmission. The cable reel is equipped with a carrying handle and disconnecter for enhanced usability. Designed with a protection degree of IP20, it offers basic protection against solid objects. Additionally, it boasts an IK07 rating, providing resistance to mechanical impacts. The cable reel is mounted on a stand, facilitating stability and ease of use in various settings.
Mounting version	WITH STAND

■ TECHNICAL CHARACTERISTICS

Cable section	1,5mm ²
Cable	H05VV-F
Wound cable power	1500W
Unwound cable power	3600W

■ PHYSICAL CHARACTERISTICS

Mounting version	WITH STAND
Material	ENGINEERING PLASTIC
Protection degree IP	IP20
Protection degree IK	IK07
Working temperature	-25°C/+40°C

■ DIMENSIONAL CHARACTERISTICS

No. of available outlets	4 NR
Cable length	40m

■ OPTIONS & VARIOUS NOTES

Options	With carrying handle
Options	With disconnecter
Catalogue notes	Cable H05VV-F (PVC)
	The maximum power supply is shown on every single item.
	Note: Scame domestic socket outlets guarantee protection degree IP54 when the lid is closed.
	Cable reels for domestic and similar applications:
	IP20D with domestic plug inserted