

751.40325-10C**AUTOMATIC REWIND CABLE REEL**
IP42 10m 3x2,5mm²EN 61242 (1997)
EN 61242 A2 (2016)
EN 61242 A1 (2008)
EN 61242 A13 (2017)Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU**■ GENERAL CHARACTERISTICS**

Commercial Series	AUTOROLLER Series
Synthetical description	AUTOMATIC REWIND CABLE REEL
Description	
The AUTOROLLER Series automatic rewind cable reel is engineered for demanding industrial environments. crafted from thermoplastic, it features a 10-meter H05VV-F cable with a section of 2.5mm ² , ensuring efficient and secure electrical transmission. With an IP42 protection degree, it offers adequate resistance against solid objects and water ingress. The reel is equipped with an automatic rewind mechanism and a disconnecter for enhanced safety and convenience. Its IK08 rating guarantees robust impact resistance. Designed for surface mounting, this cable reel combines durability with functionality, making it a reliable choice for industrial applications.	
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Cable section	2,5mm ²
Cable	H05VV-F
Wound cable power	2000W
Unwound cable power	2300W

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Material	THERMOPLASTIC
Protection degree IP	IP42
Protection degree IK	IK08

■ DIMENSIONAL CHARACTERISTICS

No. of available outlets	1 NR
Cable length	10m

■ OPTIONS & VARIOUS NOTES

Options	With automatic rewind
Options	With disconnecter
Catalogue notes	Cable H05VV-F (PVC)