SCM316B6W

FLUSH MOUNTING APPLIANCE INLET
16A 2P 3W 6h 200-250V 50/60Hz
120X120MM Screw terminals



* Product image may be indicative

CE

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA-HD[UL] Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The EUREKA-HD[UL] Series flush mounting appliance inlet is engineered for high-performance electrical applications. Designed with a 90° angled outlet, it features a 2P 3W configuration, supporting a rated current of 16A and a rated voltage of 200-250V. This inlet operates efficiently at both 50Hz and 60Hz frequencies, with a 6h hour position. It offers robust protection with an IP67 rating, ensuring resistance against dust and water ingress. Equipped with screw terminals, it guarantees secure and reliable connections. This appliance inlet is a reliable component for demanding industrial environments, providing consistent and safe power delivery.

Mounting version	FLUSH MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P 3W
Hour position	6h
Rated voltage	200-250V
Working frequency	50/60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP67
Protection degree IK	IK10
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated

DIMENSIONAL CHARACTERISTICS

Flange	120X120MM

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]