SCM316C4W

CONNECTOR
16A 2P 3W 4h 100-130V 50/60Hz
Screw terminals



* Product image may be indicative

IEC 60309-1 (2021)
IEC 60309-2 (2021)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA-HD[UL] Series
Synthetical description	CONNECTOR
Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P 3W
Hour position	4h
Rated voltage	100-130V
Working frequency	50/60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	YELLOW
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP67
Protection degree IK	IK10
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	UL classified

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000