SCM363C6W

CONNECTOR
63A 2P 3W 6h 200-250V 50/60Hz
Screw terminals



* Product image may be indicative

IEC 60309-1 (2021)
IEC 60309-2 (2021)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	EUREKA-HD[UL] Series
Synthetical description	CONNECTOR
Description	

The EUREKA-HD[UL] Series connector is engineered for robust electrical industrial applications, offering a rated voltage of 200-250V and a rated current of 63A. This connector features a 2P 3W configuration and a 6h hour position, ensuring reliable performance in demanding environments. With an IP67 protection degree, it provides superior resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a straight outlet type, it is UL classified, guaranteeing compliance with stringent safety standards. This connector is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	2P 3W
Hour position	6h
Rated voltage	200-250V
Working frequency	50/60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP67
Protection degree IK	IK10
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	UL classified