

313.1643P**PRISE MOBILE****16A 2P+T 6h 200-250V 50Hz 60Hz****Raccordement à perf. d'isolant**

* L'image du produit peut être indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Directive BT 2014/35/EU

■ CARACTÉRISTIQUES GÉNÉRALES

Série commerciale	Série OPTIMA
Description	PRISE MOBILE
Description	The connector of the OPTIMA Series is engineered for a rated voltage of 200-250V and a rated current of 16A. Featuring a 2P+E configuration and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With an IP44/IP54 protection degree, it ensures robust performance in various environments. Equipped with perforating terminals and straight type outlets, it offers reliable connectivity. For enhanced customization, a version in black is available by appending ".K" to the catalogue number, and a version with a transparent handle is available by appending ".TR" to the catalogue number.
Type de installation	
	PORTABLE

■ CARACTÉRISTIQUES TECHNIQUES

Courant nominal	16A
Pôles	2P+T
Position d'heure	6h
Tension nominale	200-250V
Fréquence d'utilisation	50Hz
	60Hz
Bornes	Raccordement à perf. d'isolant

■ CARACTÉRISTIQUES PHYSIQUES

Type de installation	PORTABLE
Couleur	BLEU
Matériau	THERMOPLASTIQUE
Indice de protection	Splash proof
Indice de protection IP	IP44/IP54
Indice de protection IK	IK08
Types de sorties disponibles	DROITE
Matériel de contact	CuZn (laiton)
Sortie du câble	PRESSE-ETOUPE

■ TÉLÉCHARGER

Dessin Technique [PDF]

Dessin Technique [DWG]

Dessin Technique [STP]

■ OPTIONS ET NOTES DIVERSES

Catalogue notes	Version également disponible en couleur noire, ajouter ".K" aux references.
	Version également disponible avec poignée transparente; ajouter ".TR" aux references.