313.1647P

PRISE MOBILE
16A 3P+N+T 6h 346-415V 50Hz 60Hz
Raccordement à perf. d'isolant

* L'image du produit peut être indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)

Directive BT 2014/35/EU

CARACTÉRISTIQUES GÉNÉRALES

Série commerciale	Série OPTIMA
Description	PRISE MOBILE

Description

The connector of the OPTIMA Series is engineered for a rated voltage of 346-415V and a rated current of 16A. Featuring a 3P+N+E configuration and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With an IP44/IP54 protection degree, it ensures robust performance in various environments. Equipped with perforating terminals and straight type outlets, it offers reliable connectivity. For an alternative appearance, a version in black is available by appending ".K" to the catalogue number.

Type de installation	PORTABLE

CARACTÉRISTIQUES TECHNIQUES

Courant nominal	16A
Pôles	3P+N+T
Position d'heure	6h
Tension nominale	346-415V
Fréquence d'utilisation	50Hz
	60Hz
Bornes	Raccordement à perf. d'isolant

CARACTÉRISTIQUES PHYSIQUES

Type de installation	PORTABLE
Couleur	ROUGE
Matériau	THERMOPLASTIQUE
Indice de protection	Splash proof
Indice de protection IP	IP44/IP54
Indice de protection IK	IK08
Types de sorties disponibles	DROITE
Matériel de contact	CuZn (laiton)
Sortie du câble	PRESSE-ETOUPE

TÉLÉCHARGER

Dessin Tecnique [PDF]
Dessin Tecnique [STP]
Dessin Tecnique [DWG]

OPTIONS ET NOTES DIVERSES

Catalogue notes	Version également disponible en couleur noire, ajouter ".K" aux references.